

All in One POS terminal PT-6200



Do small business need POS? The answer is PT-6200!

Partner Tech is pleased to announce the new revolution fanless All-in-One POS terminal PT-6200, PT-6200 is the solution for small and medium business, its an affordable yet easy to use integrated terminal, which can help small and medium business to serve customer effectively, and keep pace with competitors. The compact base embedded with 80mm thermal printer, touch screen and integrated customer display, design with attractive appearance and small footprint for counter space saving, PT-6200 can fit in with any environment installation.

Special Features:

- ▶ Fanless design
- ▶ 10.4" Touch Screen
- ▶ Magnetic Card Reader Track 1, 2, 3
- ▶ 80mm thermal printer
- ▶ Modular design for easy maintenance
- ▶ Base designed with easy cable management
- ▶ Open architecture

All in One POS terminal PT -6200



80mm Thermal receipt printer



Triple-track MSR reader



Customer display module

Technical data

LCD	10.4" TFT-LCD, resolution is 800 x 600
Touch	5-wire Resistive touch (PS/2 interface)
CPU	Intel Celeron-M Processor @ 600MHz, L2 Cache 512KB, FSB 400MHz, fanless design
Chipset	NB - Intel 82852GM SB - Intel 82801DB
Memory	184-pin DDR DIMM x 1 , System ships with 512MB as the standard
BIOS	Award System BIOS, 4M bits flash ROM
Graphics	On-Board Graphics: Intel® 852GM integrated dynamic video shared memory On board LVDS connector for LCD support Max. shared memory of 64MB
Ethernet	On-Board 10/100/1000 Ethernet controller
Audio	On-Board Audio : Realtek Two channel AC'97 2.3 Audio Codec
HDD	Internal 3.5" type IDE HDD 80GB or above
I/O Interface	4 * COM ports (COM1 & 2 are powered with DC+5V or DC+12V BIOS selection for voltage control. COM3 is powered with DC+5V or DC+12V Jumper selection control. COM4 is powered with DC+5V 1 * RJ-11 port for cash drawer(+24V) 1 * PS2 Keyboard port, auto routing for MSR, no jumper 1 * RJ-45 LAN port with activity and link LEDs 4 * USB ports 1 * DC +12V power adaptor connector
Peripherals	Triple-track MSR reader (PS/2 interface) Customer display module (serial interface) 80mm Thermal receipt printer with cutter + control board (serial interface)
Operation System	Windows XP, XP embedded, CE.Net, Linux(Fedora, Red Hat & SuSE), WEPOS
Power Supply	AC 100V~240V/DC12V/12.5A 150 watt power adaptor
Operating Temperature	0°C~40°C
Storage Temperature	-20°C~60°C
Operating & Storage Humidity	10%~80%
Color	White or Dark Charcoal
Certification	CE, FCC, UL, CUL, CB, VCCI, BSMI, 3C

